



Terni's wear layer is constructed from 4mm solid European White Oak Hardwood and its core is comprised of layers of plywood. Chevron flooring is one of the most sought after hardwood choices in the US. All of these layers combined result in a  $\frac{5}{8}$ " total plank thickness and each plank measuring 4- $\frac{3}{4}$ " in width.

## SPECIFICATIONS:

|                      |   |                     |
|----------------------|---|---------------------|
| BEVEL                | : | Micro               |
| COLLECTION           | : | Capri               |
| COLOR                | : | Natural             |
| CONSTRUCTION         | : | Engineered Hardwood |
| FINISH               | : | Oil                 |
| GRADE                | : | Rustic              |
| INSTALLATION PATTERN | : | Chevron             |
| JANKA RATING         | : | 1360                |
| OIL FINISH           | : | Natural             |

## INSTALLATION METHOD: NAIL / GLUE / FLOATING

|                  |   |                                        |
|------------------|---|----------------------------------------|
| PLANK CONNECTION | : | Tongue and Groove                      |
| PLANK LENGTH     | : | Random Up to 7ft (Most pieces are 7ft) |
| PLANK THICKNESS  | : | $\frac{5}{8}$ "                        |
| PLANK WIDTH      | : | 4- $\frac{3}{4}$ "                     |
| Sq. Ft. PER BOX  | : | 11.25                                  |
| TEXTURE          | : | Wire Brushed                           |
| WEAR LAYER       | : | 4mm                                    |
| WOOD SPECIES     | : | European White Oak                     |
| WT PER BOX       | : | 23 lbs                                 |

