



Pordenone's wear layer is constructed from 4mm solid European White Oak Hardwood and its core is comprised of two to nine-layer plywood. Straight Plank flooring is one of the most sought after hardwood choices in the US. All of these layers combined result in a  $\frac{5}{8}$ " total plank thickness and each plank measuring 9- $\frac{1}{2}$ " in width.

## SPECIFICATIONS:

|                      |   |                     |
|----------------------|---|---------------------|
| BEVEL                | : | Micro               |
| COLLECTION           | : | Novara              |
| COLOR                | : | Natural             |
| CONSTRUCTION         | : | Engineered Hardwood |
| FINISH               | : | UV Lacquer          |
| GRADE                | : | ABCD (Character)    |
| INSTALLATION PATTERN | : | Straight Plank      |
| JANKA RATING         | : | 1360                |
| OIL FINISH           | : | Natural             |

## INSTALLATION METHOD:

|                  |   |                                        |
|------------------|---|----------------------------------------|
| PLANK CONNECTION | : | Tongue and Groove                      |
| PLANK LENGTH     | : | Random Up to 7ft (Most pieces are 7ft) |
| PLANK THICKNESS  | : | $\frac{5}{8}$ "                        |
| PLANK WIDTH      | : | 9- $\frac{1}{2}$ "                     |
| Sq. Ft. PER BOX  | : | 22.76                                  |
| TEXTURE          | : | Wire Brushed                           |
| WEAR LAYER       | : | 4mm                                    |
| WOOD SPECIES     | : | European White Oak                     |
| WT PER BOX       | : |                                        |

